# 149-10A

## HIGH VOLTAGE DIGITALMETER



AC/DC 10kV Input Impedance 1000M $\Omega$ Compact, Lightweight

#### **Outline**

The 149-10A is a digital voltmeter that can measure high voltages up to a 10kV AC and DC at high accuracy.

Its high input impedance (1000M $\Omega$ ) makes it suitable for measurement of high impedance voltage circuits.

Since it has a high accuracy despite its small size and light weight, it can also be easily used as a portable calibrator.

#### **Features**

- Measures high voltages (AC/DC) up to 10kV
- Large 4 1/2 digits LED display
- High measurement accuracy and high input impedance
- Light weight and compact design
- For output voltage calibration of withstanding voltage testers and insulation testers

### **Specifications**

■ DC voltage

0.500 to 10.000kV Measurement range  $\pm (0.5\% \text{ rdg} + 0.03\% \text{ range})$ Accuracy

Maximum allowable input voltage DC: ±14kV Pulse: 15kV peak

■ AC voltage

0.500 to 10.000kV Measurement range Accuracy  $\pm (1\% \text{ rdg} + 0.05\% \text{ range})$ 

Maximum allowable input voltage

11kVrms (sine wave 50 to 60Hz) Pulse: 15kV peak

■ Display LED, 7 segments ■ Voltmeter type Double integration

AC: Average value response, sine wave value

calibration 3 sampling/s

 $1000 \mathrm{M}\Omega \pm 2\%$ ■ Input impedance

■ Power requirement 100VAC ±10%, 50/60Hz\*

■ Power consumption Approx. 10VA

 $134W \times 164H \times 270D \text{ mm}$ ■ Dimensions (MAX)

 $(140W \times 189H \times 350D \text{ mm})$ 

■ Weight Approx. 3kg

High voltage test lead (TL05-TOS)  $\times$  1 Accessories High voltage coaxial cable (HTL-2.5DH)  $\times$  1

<sup>\*</sup> Nominal voltages of 110V, 120V, 220V, 230V and 240V available as factory options.